













## Power Supplies

TYPE	LXS-XX1	DR-4524	DR-75-24	DR-120-24	DRP-240-24		
Photo							
Schematic							
INPUT							
Supply voltage range	230 VAC (185...265 VAC)		230 VAC (85...264 VAC)				
OUTPUT							
Number of outputs	1						
Typical output voltage	24 VDC	15 VDC	12 VDC	24 VDC			
Maximum output current	1 A	1,6 A	2 A	2 A	3,2 A	5 A	10 A
Basic accuracy	$\leq 2\%$			$\leq 1\%$			
Voltage ripple	$\leq 50$ mVpp		$\leq 480$ mVpp	$\leq 150$ mVpp	$\leq 80$ mVpp		
Maximum output power	24 W		48 W	75 W	120 W	240 W	
OTHER							
Short circuit protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Over temperature protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Over voltage protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Efficiency	~ 80%			~ 84%			
Galvanic isolation	input / output						
Galvanic isolation (test)	500 VAC		3000 VAC				
Working temperature	0...70°C		-10...60°C				
Output voltage signalization	LED						
Protection (housing / terminals)	IP20 / IP20		IP30 / IP20	IP20 / IP20			
Mounting	DIN rail						
DOCUMENTS							
Data sheet	 <a href="#">Download</a>	 <a href="#">Download</a>	 <a href="#">Download</a>	 <a href="#">Download</a>	 <a href="#">Download</a>		