







Level triggered indicators

| TYPE | LXP-217 | LXP-21K |
|----------------------------------|--|--|
| Photo |  |  |
| Schematic |  |  |
| INPUT | | |
| Current | 3,5...22 mA | |
| Voltage drop | ≤ 5,5 V | |
| OUTPUT | | |
| Number of outputs | 2 | |
| PNP Open Collector output | 0,8 A / 24 VDC | |
| Switching contacts | 6 A / 230 VAC | |
| Action indicator | LED | |
| POWER SUPPLY | | |
| Supply voltage range | 24 VDC (12...30 VDC) | 24 VDC (20...30 VDC) |
| Power supply current | ≤10 mA | ≤30 mA |
| OTHER | | |
| Basic accuracy | ≤ 0,1% | |
| Galvanic isolation | input / output, power supply | input / output / power supply |
| Galvanic isolation (test) | 1500 VAC | |
| Working temperature | 0...70°C | |
| Protection (housing / terminals) | IP20 / IP20 | |
| Mounting | DIN rail | |
| CONFIG | | |
| Config | DIP switch | |
| Threshold adjustment | multiturn potentiometer | |
| Configurable parameters | output: min/max; hysteresis | |
| DOCUMENTS | | |
| Data sheet |  Download |  Download |